Saves Energy!

5-2 Programmable Thermostat

PH521

For Use On:
24 volt: Single stage heat pumps and 2 heat/1 cool heat pump systems with auxiliary and or emergency heat

Not For Use On:
Conventional systems
Non Heat Pump Systems
Electric baseboard heat (120/240)
3 Wire zone values

Electrical Ratings:
1.5 Amps per terminal at 24 Volts AC

Terminals – W2, Y, E, R, B/O, C, G
Temperature Control: 45° F to 90°F (7°C to 32°C)

UPC Code – 0 21079 11521 1

Master Carton - 10 units

Features - continued
▪Separate weekday and weekend programs

▪Preprogrammed – 4 periods per day
▪Program defeat (manual/digital mode)
▪Exclusive Speed Slide ™

▪Programmable (4 digits) keyboard lock
▪Adjustable heat/cool temperature limits
▪Dual power – 2 AA batteries included
▪Backlight display
▪Celsius or Farenheit
▪Temperature hold
▪Temporary temperature override
▪Temporary compressor protection (service mode)
▪Adjustable temperature swing 1-9
▪Calibration feature
▪Wallplate available
▪Dual fuel

LUX PRODUCTS CORPORATION

6000 Commerce Parkway ●Suite I • Mount Laurel, NJ 08054 •
● 800 628-4309 • Fax (856) 234-7825

4/17/2012